

Instructions for use Silvanol rumeni (yellow) and Silvanol brezbarvni (colorless)

Composition

Water-based inorganic boron component, pigments.

Features

Silvanol effectively protects the wood from insects and rot, is not flammable and does not contain any volatile toxic components. Protected wood is odorless, non-toxic to the touch and does not contain chromium compounds. Protected wood with no additional surface protection with stain coatings (e.g. Silvanol stain B) should not be exposed to rain (possible washing-off of protective components).

Purpose of use

For durable and effective protection of wooden roof constructions.

Method of use

Methods for application of products are: coating, dipping and drenching. For application of product we use a brush, designed for water systems.

Consumption

With 1 kg of Silvanol yellow or Silvanol colorless we can protect approx. 4 – 5 m² of wooden surface, depending on the type of surface treatment and the quality of the wood.

Cleaning tools

After work we wash tools with water and detergent.

Safety at Work

We recommend use of personal protection equipment. Fire protection measures are also necessary. It is not recommended using product on existing roof structures at temperatures around 0 degrees Celsius, as a risk of icy surface presents danger for worker.

Storage and expiration date

Store in original unopened packaging in a place inaccessible to children and animals. Product must be stored at temperatures higher than 0 degrees Celsius. Best before: two years after production date.

Tested

Biotechnical Faculty, Department of Wood Science and Technology, University of Ljubljana.